


Drawings are not to scale.

## QuickEdge® Decorative Protective Trim

### Flexible Embossed Vinyl Aluminum Core QuickEdge® Trims

#### 1/2" Trim


for 3/8" to 1/2" Edges  
Grips edges from  
.250" to .500" thick



PART NO.	DESCRIPTION	CARTON FEET
75001582	Black Sof-Tone	150
75001620	White Sof-Tone	150

#### Pinch Top Single Lip Trim

for 1/8" Edges  
Grips edges from  
.060" to .170" thick



PART NO.	DESCRIPTION	CARTON FEET
75001585	Black Sof-Tone	400
75001623	White Sof-Tone	400

#### "Q" Trim


for 3/16" to 1/4" Edges  
Grips edges from  
.135" to .250" thick



PART NO.	DESCRIPTION	CARTON FEET
75001583	Black Sof-Tone	250
75001621	White Sof-Tone	250

#### Standard Double Lip Trim


for 1/32" to 1/8" Edges  
Grips edges from  
.032" to .125" thick



PART NO.	DESCRIPTION	CARTON FEET
75001584	Black Sof-Tone	400
75001622	White Sof-Tone	400

#### Standard Single Lip Trim


for 1/8" to 3/16" Edges  
Grips edges from  
.090" to .190" thick



PART NO.	DESCRIPTION	CARTON FEET
75000346	White Sof-Tone	400
75000348	Black Sof-Tone	400
75001234	White Sof-Tone	100
75001309	Black Sof-Tone	100

#### Minitrim

for 1/32" Edges  
Grips edges from  
.010" to .050" thick



PART NO.	DESCRIPTION	CARTON FEET
75001586	Black Sof-Tone	500
75001624	White Sof-Tone	500

### Advantages and Physical Characteristics

**Environmentally Safe Vinyl** - Embossed PVC extrusions with non-cadmium stabilizers

**Segmented Aluminum Core** - Type 50-52 Rockwell 38, .024" thick

**Flexible Durometer** - All parts are 65 durometer except the Standard Double Lip Trims which are 80 durometer hardness (share A 15 second delay)

**Tensile Strength** - 2200 P.S.I. / Minimum

**Elongation** - 300% minimum

**Cold Impact** - Will withstand 1-1/2 foot pound impact at -20° F

**Heat Resistance** - 150° F maximum for continuous use

**Flammability** - Self extinguishing, passes Federal Spec. FMVSS-302

